

**Courants admissibles pour un maximum de trois conducteurs en cuivre dans une canalisation ou un câble.**

**Sur une base d'une température ambiante de 30 ° C \***

	COURRANT ADMISSIBLE +++					
	60 °C	75 °C	85-90 °C	110 °C	125 °C	200 °C
GROSSEUR AWG KCMIL	TYPE TW	TYPES RW75, TW75	TYPES R90, W90, T90 NYLON	VOIR NOTE 1	VOIR NOTE 1	VOIR NOTE 1
			ISOLANT DE PAPIER			
			CÂBLE A ISOLANT MINERAL **			
14	15	15	15	30	30	30
12	20	20	20	35	40	40
10	30	30	30	45	50	55
8	40	45	45	60	65	70
6	55	65	65	80	85	95
4	70	85	85	105	115	120
3	80	100	105	12	130	145
2	100	115	120	125	145	165
1	110	130	140	160	170	190
0	125	150	155	190	200	225
00	145	175	185	215	230	250
000	165	200	210	345	265	285
0000	195	230	235	275	310	340
250	215	255	265	315	335	---
300	240	285	295	345	380	---
350	260	310	325	390	420	---
400	280	335	345	420	450	---
500	320	380	395	470	500	---
600	355	420	455	525	545	---
700	385	460	490	560	600	---
750	400	475	500	580	620	---
800	410	490	515	600	640	---
900	435	520	555	---	---	---
1000	455	545	585	680	730	---
1250	495	590	645	---	---	---
1500	520	625	700	785	---	---
1750	540	650	735	---	---	---
2000	560	665	775	840	---	---
COL.1	COL.2	COL.3	COL.4	COL.5	COL.6	COL.7