



**Nombre maximal de conducteurs de même diamètre
pour chaque grosseur nominale de conduit ou de tube.**

Grosseur du conduit ou du tube (désignation métrique)		1/2 (16)	3/4 (21)	1 (27)	1¼ (35)	1½ (41)	2 (53)	2½ (63)	3 (78)	3½ (91)	4 (103)	4½ (116)	5 (129)	6 (129)
Conducteur														
Type	AWG,kcmil													
600 V sans	14	8	15	25	43	59	97	139	200	200	200	200	200	200
enveloppe	12	6	11	19	33	45	74	106	164	200	200	200	200	200
	10	5	8	14	24	33	55	78	121	162	200	200	200	200
R90XLPE	8	2	4	7	13	18	30	43	67	90	116	146	183	200
RW75XLPE	6	1	3	5	10	13	22	32	50	67	86	108	136	196
RW90XLPE	4	1	2	4	7	10	16	23	36	48	62	78	98	142
	3	1	1	3	6	8	14	19	30	41	53	66	83	120
	2	1	1	3	5	7	11	16	25	34	44	55	70	101
	1	1	1	1	3	5	8	12	19	25	33	41	52	75
	1/0	0	1	1	3	4	7	10	16	21	27	34	44	63
	2/0	0	1	1	2	3	6	8	13	17	23	29	36	53
	3/0	0	1	1	1	3	5	7	11	14	19	24	30	44
	4/0	0	0	1	1	1	4	6	9	12	15	20	25	36
	250	0	0	1	1	1	3	4	7	10	13	16	21	30
	300	0	0	1	1	1	2	4	6	8	11	14	18	25
	350	0	0	0	1	1	2	3	5	7	9	12	16	23
	400	0	0	0	1	1	1	3	5	6	8	11	14	20
	450	0	0	0	1	1	1	3	4	6	8	10	13	18
	500	0	0	0	1	1	1	2	4	5	7	9	11	17
	600	0	0	0	0	1	1	1	3	4	5	7	9	13
	700	0	0	0	0	1	1	1	3	4	5	6	8	12
	750	0	0	0	0	1	1	1	2	3	4	6	8	11
	800	0	0	0	0	1	1	1	2	3	4	5	7	10
	900	0	0	0	0	0	1	1	1	3	4	5	6	9
	1000	0	0	0	0	0	1	1	1	2	3	4	6	9
	1250	0	0	0	0	0	1	1	1	2	3	3	5	7
	1500	0	0	0	0	0	0	1	1	1	1	3	4	6
	1750	0	0	0	0	0	0	1	1	1	1	2	3	5
	2000	0	0	0	0	0	0	1	1	1	1	1	3	4