



**Nombre maximal de conducteurs de même diamètre
pour chaque grosseur niminale de conduit ou de tube.**

Grosseur du conduit ou du tube (désignation métrique)		1/2 (16)	3/4 (21)	1 (27)	1¼ (35)	1½ (41)	2 (53)	2½ (63)	3 (78)	3½ (91)	4 (103)	4½ (116)	5 (129)	6 (129)
Conducteur														
Type	AWG, kcmil													
TW75 nylon	14	12	22	36	62	85	140	200	200	200	200	200	200	200
T90 nylon	12	9	16	26	45	62	102	145	200	200	200	200	200	200
	10	4	8	13	23	31	52	74	114	153	197	200	200	200
	8	3	5	9	16	22	36	52	80	100	138	173	200	200
	6	1	4	6	11	16	26	37	58	80	100	125	157	200
	4	1	2	4	7	9	16	23	35	47	61	77	96	140
	3	1	1	3	6	8	13	19	30	40	52	65	82	118
	2	1	1	2	5	7	11	16	25	34	43	55	69	99
	1	1	1	2	3	5	8	12	18	25	32	40	51	73
	1/0	0	1	1	3	4	7	10	15	21	27	34	42	62
	2/0	0	1	1	2	3	6	8	13	17	22	28	35	51
	3/0	0	1	1	1	3	5	7	11	14	19	23	29	43
	4/0	0	0	1	1	1	4	5	9	12	15	19	24	35
	250	0	0	1	1	1	3	4	7	10	12	16	20	29
	300	0	0	1	1	1	2	4	6	8	11	13	17	25
	350	0	0	0	1	1	2	3	5	7	9	12	15	22
	400	0	0	0	1	1	1	3	5	6	8	10	13	19
	450	0	0	0	1	1	1	2	4	6	7	9	12	17
	500	0	0	0	1	1	1	2	4	5	7	9	11	16